Puerto Rico Portable Air Conditioning www.PuertoRicoPortableAc.com

25 Ton Portable Air Conditioning & Heat Package

General Description

YORK International portable air-conditioner package is specifically engineered for commercial and industrial applications. Packaged by YORK International. Controls and dehumidification offer easy added flexibility. Package is mounted, fork lifted, craned and transported within a compact footprint. Power and duct connections secured in seconds ensure rapid setup/teardown and minimized costs.



Technical Data

General

Unit Model ZF300E36 Ambient Operating Range 45º-125º F

Refrigerant Circuits 2

Supply Air Flow Range 6,000-12,000 CFM Design Supply Air Flow 10,000 CFM

Design Supply Air Flow 10,000 C Refrigerant 410 A

Unit Dimensions

9	Skid/Frame	Skid/Frame/Trailer
Length	136"	172"
		(w/ trailer tongue)
Width	92"	92"
Height	$52-\frac{5}{8}$ "	$52-\frac{5}{8}$ "
Shipping Weigh	nt 4,500 lb:	s. 4,650 lbs.

Electrical Data

Single Point Power Supply 460V/3Ø/60Hz
Connections (4) Series 16 Cam Type

Electric Heat 25 kW

Minimum Circuiting Amps

Cooling Only 60 Amps Heating Only 70 Amps

Air Conditioner & Heat Features

Constant Volume 25 kW Electric Heat Simplicity Controls

Two independent 12.5-ton scroll refrigerant systems. Each circuit includes expansion valve, liquid line filter drier, high-pressure switch, suction freezestat and low pressure/loss charge switch.

Cooling Capacity

Actual capacities subject to leaving temperatures, airflows and ambient conditions

CFM	WB (°F)	Total MBH	Sensible Capacity MBH Entering Dry Bulb (°F)			
			86	77	68	
12,000	67	325	324	214	105	
9,000	67	279	279	195	111	
6,000	67	213	213	156	99	
*Capacities are rated on 95 F ambient air						